



## **SB1587 Adhesive Bond Limited Lifetime Warranty SB1587 Concrete Subfloor Moisture Protection Limited Warranty**

### **SB1587 Adhesive Bond Limited Lifetime Warranty**

Nydree Flooring warrants that SB1587 adhesive is free from manufacturing defects and will bond all Nydree Engineered Hardwood Flooring to those substrates common to hardwood flooring installation for the lifetime of the flooring. This warranty is to the original purchaser of the flooring and is non-transferable. The SB1587 adhesive must be used in strict accordance with Nydree's installation instructions. Failure to follow these specific installation instructions completely will void this warranty. Loss of adhesion due to subfloor moisture, topical moisture, including flooding is not covered under this warranty. SB1587 should never be used over cutback residue or over any type of vinyl/VCT flooring.

### **SB1587 Concrete Subfloor Moisture Protection Limited Warranty**

***Calcium Chloride results up to 15 lbs./1000 sf/24 hrs and in-situ Relative humidity results up to 87%.***

Nydree Flooring warrants that SB1587 will bond and will protect all Nydree Flooring installations against moisture damage coming from the concrete subfloor only (e.g.: cupping, end lifting, warping, buckling) for a period of ten (10) years provided:

- Any moisture readings in the concrete slab at the time of installation or after installation does not exceed 15 lbs./1000 sf /24 hours or does not exceed 87% in-situ relative humidity, certified by the required number of Calcium Chloride Tests (ASTM F1869) or required number of in-situ Relative Humidity Tests (ASTM F2170). The protocol for either moisture test must be followed precisely for warranty consideration. The preferred moisture testing method is In-situ Relative Humidity, since it can identify potential moisture problems deep within a concrete slab. If both tests are performed, the in-situ RH test is always the qualifying standard.
- The adhesive must be applied with the standard 1/4" x 1/4" x 7/16" V-Notch trowel at a rate that does not exceed 55 square feet per gallon.
- The adhesive must cover 100% of the concrete substrate.
- There must be 85% transfer of adhesive between the concrete substrate and flooring.
- The SB1587 adhesive is used in strict accordance with Nydree Flooring's installation instructions including surface preparation (no concrete sealer or curing compound) and expansion spacing. Failure to follow these specific installation instructions completely will void this warranty.

***Calcium Chloride results up to 18 lbs./1000 sf/24 hrs and in-situ Relative humidity results up to 95%.***

Nydree Flooring warrants that SB1587 will bond and will protect all Nydree Flooring installations against moisture damage coming from the concrete subfloor only (e.g.: cupping, end lifting, warping, buckling) for a period of ten (10) years provided:

- The adhesive must be applied with a 5/16" x 5/16" x 7/16" V-Notch trowel with Moisture Plus spacers at a rate that does not exceed 35 square feet per gallon.
- The adhesive must cover 100% of the concrete substrate.
- There must be 85% transfer of adhesive between the concrete substrate and flooring.
- The SB1587 adhesive is used in strict accordance with Nydree Flooring's installation instructions including surface preparation (no concrete sealer or curing compound) and expansion spacing. Failure to follow these specific installation instructions completely will void this warranty.

The Moisture Protection warranty above is contingent upon the following:

- An evaluation of a potential claim by a Nydree Flooring representative in advance of any replacement work, and a copy of the original materials and installation invoice(s). Nydree reserves the right to collect flooring samples, adhesive, patching compounds and concrete samples from the jobsite. Any repairs or replacement of flooring conducted prior to evaluation and written authorization will void all warranties.
- The SB1587 is used in accordance with Nydree Flooring's most recent published literature.
- The wood flooring must be installed in accordance with Nydree Flooring's most recent published literature pertaining to SB1587 glue down installations, including but not limited to, wood flooring acclimation, surface preparation, expansion space, jobsite temperature, relative humidity and air flow requirements.
- These warranties do not cover damage (e.g.: cupping, end lifting, warping, buckling) due to flooding, hydrostatic head, puddling, drainage or leakage, improper maintenance, topical moisture, low/excessive relative humidity and/or temperature, substrate irregularities, friable substrates or surface contamination or any issues not related to excessive moisture proven to be coming through the SB1587 membrane.
- Proper SB1587 coverage and transfer rates.
- Misuse; improper alteration, modification, or dilution of product; exposure to corrosive materials or contaminants; industrial applications subject to chemical or mechanical abuse; improper maintenance or use of cleaning products; or failure to use product within its shelf life will void this warranty.

In the event of a valid claim under any of these warranties, Nydree Flooring will pay to repair or replace on a square foot basis the portion(s) of the installation that is proven to be defective. This payment is to include all reasonable materials and labor only. Nydree Flooring is not responsible for workmanship not in accordance with Nydree Flooring's most recent published literature, abuse, misuse, or losses due to delays, relocation expenses or any other incidental and consequential damages. All of these warranties apply to the original purchaser only and are non-transferable. Nydree Flooring will repair or replace the affected flooring one time only.

The SB1587 Adhesive Bond Limited Lifetime Warranty and SB1587 Concrete Subfloor Moisture Protection Limited Warranty is sellers only warranty. Seller makes no other express warranties, and seller makes no implied warranties of merchantability and fitness for a particular purpose. In no event shall seller be liable for incidental and consequential damages caused by breach of warranty. Some states do not allow limitations on how long an implied warranty lasts, so the above limitation may not apply to you. Some states do not allow the exclusion or limitation of incidental or consequential damages, so the above limitation or exclusion may not apply to you. This warranty gives you specific legal rights, and you may also have other rights that vary from state to state.